

## **BOTTOM MOUNT CABINETS**



PU401

## **Key Features:**

Stainless Steel Interior & Exterior

Designed To Operate In 43°C Ambient

Built-In Air Rear Duct For Even Temperature Distribution

R290 Hydrocarbon Refrigerant

Zero ODP Injected Polyurethane Insulation

-2 / +4°C Refrigerator Temperature Range

Electronic Controller With Easy Read LCD Screen

Door Locks Fitted As Standard

**Rifle Bore Coated Evaporators** 

Ergonomic Flush Door Handle

Non Gastronorm Shelving System - (GN1/1 Pans Can Fit On Shelves) - Anti Tilt Slides

Hi / Lo Audio Visual Temperature Alarms

Condensing Unit Safety System To Protect Compressor From Blocked Condensers

Self Closing Door

Heavy Duty Brake & Swivel Castors

Waste Heat Recovery Condensate Vaporiser System

Precision's durable all stainless steel cabinets have been designed to provide commercial caterers with reliable, energy and cost efficient refrigerated storage solutions. Proudly designed in the UK, these slimline cabinets are capable of meeting the highest demands of commercial kitchens all around the world especially when space is at a premium.



Non-Gastronorm Shelving System With Anti-Tilt Slides

## **Options:**

Extra Std Nylon Coated Shelves / Slides

Extra Shelf / Pan Slides

Fish Shelving - 7 x GN1/1 - 100mm Deep - Stainless Steel Pans & Slides per section with Slime Trays

Stainless Steel Back


Left Hand Hinged Door


Adjustable Legs

Precision Connect



## **BOTTOM MOUNT CABINETS**





Model	MPU401	LPU401
Туре	Refrigerator	Freezer
Material	ST/ST Int/Ext	ST/ST Int/Ext
Shelf Size	418 x 530mm	418 x 530mm
Number of Shelves	4	4
Max Number of Shelves (100mm Spacing)	12	12
Temperature Range	-2 / +4°C	-18 / -22°C
Exterior WxDxH (mm)	600x705x1985	600x705x1985
Net Usable Volume (litres)	261	261
Weight (KG)	110	120
Refrigerant / GWP	R290 /3	R290 /3
Refrigeration Watts (+45°C Condensing)	373	495
Evaporating Temp	-10°C	-30°C
Heat Rejection Watts*	560	743
Noise Output (dBa)	68	69
Power	220 / 50 / 1	220 / 50 / 1
Running Amps	1.3	2.9
Total Electrical Load - kW	0.29	0.64
Energy Consumption / 24hrs - kWh**	1.14	6.03
Energy Consumption / Year (AEC) - kWh**	416	2201
Energy Efficiency Class**	С	E

\* Heat Rejection is taken at the listed evaporating and condensing condition. Watts is calculated using total power of the cabinet. \*\* Tested to BS EN ISO 22041

We are constantly innovating and improving our products. Please scan QR code for the most up-to-date version of this spec sheet: